1% of FSO non-linearity Temperature compensated 4 to 20mA output 1,450 PSI (100 Bar) operation Compatible with Ammonia & compressor oils



**Dimensions (11mm stroke version)** 

4.73 [120.14]

4.297

[109.14] 20 ± 1 mA POSITION

> 3.937±.010 [100.0±0.25]

> > ¢ .650 [16.5]

3/4-16UNJF-24

0-RING GROOVE # .660+.002 X .094+.015 WIDE

SURFACE FINISH - 32

4 + 1

mA positio

.25 [6.4]

.03

.187 [4.75]

The PCI-650 Series transmitter is extremely rugged and accurate. It features a spring-loaded guided probe with a hard tip, and a removable electronic module to facilitate installation into pressurized devices such as valves and actuators. The PCI-650 is designed to operate in refrigerants (including ammonia) and compressor oils, as well as many other compatible fluids.

## FEATURES

- 1% of FSO non-linearity, maximum
- Uses LVDT technology for excellent stability and temperature performance
- Infinite resolution
- EMI/EMC/ESD protected
- High reliability
- High vibration/shock withstanding
- ATEX certification
- Supplied with mating cable
- Calibration certificate provided with each unit



NW27



## **APPLICATIONS**

- Refrigerant compressor capacity volume control valves
- Refrigerant compressor oil systems
- Slide valves
- Short stroke hydraulic actuators
- Other fluid and gas pressure applications
- Applications requiring media isolation

PCI-650 Series LVDT Rev 2

HIRSCHMANN

2.559±.010

[65.0±0.25]

CONNECTOR TYPE GSSR 300 P/N 933114-100

A

2.992±.030 [76.0±0.76]

.51 [13.0]

0

## **Performance specifications**

Parameter	Value	Comment
Stroke range	0 to 11mm (0.433 inch)	Other strokes can be
	0 to 40mm (1.575 inch)	created for high volume
	0 o 70mm (2.756 inches)	OEM applications
	0 to 85mm (3.346 inches)	
	0 to 100mm (3.937 inches)	
Supply Voltage	12 to 28 VDC	
Output	4 to 20mA DC	
Non-linearity	±1% of FSO, maximum	
Resolution	"Infinite"	Analog amplification
Maximum operating pressure	100 Bars (1,450 PSI)	
Operating Temperature	-4 to +176°F (-20 to +80°C)	Electronics
	-40 to +248°F (-40 to +120°C)	LVDT sensor
Operating pressure	1,450PSI (100 bars) maximum	From o-ring to tip of probe
Certification	ATEX	

**Note:** FSO (Full Scale Output) is the largest absolute value of the outputs measured at the ends of the stroke range

联系方式



广东省深圳市南山区创业路恰海广场东座2407 邮编:518000 电话:+86 755 2641 9890 传真:+86 755 2641 9680 电子邮箱:sales@bill-well.com