

Model 832M1 Accelerometer



Triaxial Piezoelectric Accelerometer
<22 μ A Current Consumption
Wide Bandwidth to 6kHz
Circuit Board Mountable



The Model 832M1 is a low cost, board mountable triaxial accelerometer. Featuring stable piezo-ceramic crystals, the accelerometer incorporates full power and signal conditioning with a maximum current consumption of 22 micro-amps. The model 832M1 is available in $\pm 25g$ to $\pm 500g$ ranges and provides a flat frequency response up to greater than 6kHz. The standard model 832 offers the same envelope with a lower maximum current consumption of 4 micro-amps.


FEATURES

- $\pm 25g$ to $\pm 500g$ Dynamic Range
- Low Cost Triaxial
- Hermetically Sealed
- Piezo-ceramic Crystals
- -40° to $+125^{\circ}C$ Operating Range
- Single Axis Configurations Available

APPLICATIONS

- Asset Monitoring
- Data Loggers
- Impact Monitoring
- Machine Health Monitoring
- System Wake-Up Switch
- Embedded Applications

dimensions



Model 832M1 Accelerometer

performance specifications

All values are typical at +24°C, 100Hz and 3.3Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice. Standard product parameters are described in PSC-1001 for Embedded AC Accelerometers.

| Parameters | | | | | | Notes |
|--|-----------------------------------|-----------------|-----------------|-----------------|-----------------|-----------|
| DYNAMIC | | | | | | |
| Range (g) | ±25 | ±50 | ±100 | ±200 | ±500 | |
| Sensitivity (mV/g) | 50.0 | 25.0 | 12.5 | 6.25 | 2.5 | ±30% |
| Frequency Response (Hz) | 2-6000 | 2-6000 | 2-6000 | 2-6000 | 2-6000 | ±2dB |
| Natural Frequency (Hz) | >10000 | >10000 | >10000 | >10000 | >10000 | |
| Non-Linearity (%FSO) | ±2 | ±2 | ±2 | ±2 | ±2 | |
| Transverse Sensitivity (%) | <10 | <10 | <10 | <10 | <10 | |
| Shock Limit (g) | 5000 | 5000 | 5000 | 5000 | 5000 | |
| ELECTRICAL | | | | | | |
| Bias Voltage (Vdc) | Exc Voltage / 2 | Exc Voltage / 2 | Exc Voltage / 2 | Exc Voltage / 2 | Exc Voltage / 2 | |
| Total Supply Current (µA) ¹ | <22 | <22 | <22 | <22 | <22 | |
| Excitation Voltage (Vdc) ³ | 3.3 to 5.5 | 3.3 to 5.5 | 3.3 to 5.5 | 3.3 to 5.5 | 3.3 to 5.5 | |
| Output Impedance (Ω) | <100 | <100 | <100 | <100 | <100 | |
| Insulation Resistance (MΩ) | >100 | >100 | >100 | >100 | >100 | @100Vdc |
| Broadband Noise (µV) | 110 | 90 | 50 | 40 | 50 | 2Hz-10kHz |
| Spectral Noise (µg/√Hz) | 120 | 160 | 160 | 160 | 600 | @ 10Hz |
| Spectral Noise (µg/√Hz) | 40 | 40 | 40 | 40 | 160 | @ 100Hz |
| Spectral Noise (µg/√Hz) | 20 | 16 | 16 | 16 | 80 | @ 1000Hz |
| Warm-Up Time (msec) | 30 | | | | | |
| Shielding | 100% | | | | | |
| Ground Isolation | Isolated from Mounting Surface | | | | | |
| ENVIRONMENTAL | | | | | | |
| Temperature Response (%) | -20/+30 from -40°C to +125°C | | | | | |
| Operating Temperature (°C) | -40 to +125 | | | | | |
| Storage Temperature (°C) | -40 to +125 | | | | | |
| PHYSICAL | | | | | | |
| Sensing Element | Ceramic (shear mode) | | | | | |
| Case Material | Ceramic Base, Nickel Silver Cover | | | | | |
| Weight (grams) | 3.0 | | | | | |

¹ A lower current consumption of 4 micro-amperes is available on model 832.

² The model 832M1 is not to be reflow soldered at high temperature, manual soldering is recommended. See application note.

³ The model 832M1 can be operated with 2.8V excitation but the full-scale range will be limited.

Calibration supplied: CS-SENS-0100 NIST Traceable Amplitude Calibration at 100Hz

ordering info

PART NUMBERING Model Number+Range

832M1-GGGG

|
|_____ Range (0200 is 200g)

Example: 832M1-0200
Model 832M1, 200g

联系方式



深圳市亿为测控电子有限公司
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000

电话：+86 755 2641 9890 传真：+86 755 2641 9680

电子邮箱：sales@bill-well.com