

### 316L SS Pressure Sensor High Pressure Sealed Gage, Absolute

#### 89 Series

The 89 series is a small profile, media compatible, piezoresistive silicon pressure sensor packaged in a 316L stainless steel housing featuring 5/16-32 UNEF threads and can be welded in place. The 89 is designed for high pressure OEM applications where compatibility with corrosive media is required.

The sensing package utilizes silicone oil to transfer pressure from the 316L stainless steel diaphragm to the sensing element.



#### FEATURES

- Weldable and Threaded Process Fittings or O-Ring Mount
- -40°C to +125°C Operating Temperature Range
- $\pm 0.25\%$  Pressure Non Linearity
- Solid State Reliability

#### APPLICATIONS

- Hydraulic Controls
- Process Control
- Process Calibrators
- Refrigeration/Compressors

# 89 Series

## Product Definition

Model	Pressure Ranges	Type (G = Gage A = Absolute D = Differential, S = Sealed Gage)	Span (typ)	Supply Voltage Current		Operating Temperature	Unique Feature
<a href="#">89U</a>	0 – 1000, 3000, 5000, 10Kpsi	A, S	See Sensitivity		1.5mA	-40°C to +125°C	Small profile 5/16-32 UNEF Threads No substrate
<a href="#">89C</a>	0 – 1000, 3000, 5000, 10Kpsi	A, S	100mV		1.5mA	-40°C to +125°C	Small profile 5/16-32 UNEF Threads 6-Pad substrate
<a href="#">89CV</a>	0 – 1000, 3000, 5000, 10Kpsi	A, S	100mV	10Vdc		-40°C to +125°C	Small profile 5/16-32 UNEF Threads 4-Pad substrate

## 联系方式



深圳市亿为测控电子有限公司  
Shenzhen Bill-Well Measurement & Control Electronics Co., Ltd.

广东省深圳市南山区创业路怡海广场东座2407 邮编：518000

电话：+86 755 2641 9890 传真：+86 755 2641 9680

电子邮箱：sales@bill-well.com